

DONMAR SKYROOF® 860 Spoiler Sunroof Warranty

LIMITED THREE YEAR WARRANTY

DONMAR Enterprises, Inc. warrants SKYROOF Spoiler Sunroofs against defective materials and workmanship, while under normal use and service, to the original purchaser, for three (3) years or 36,000 miles from the date of installation. This warranty is not transferrable. The sunroof must be properly installed by an Authorized Professional Installation Center. EXCEPTION: No vandalism or glass breakage will be covered. *No other express or implied warranties are given and this warranty is limited as follows:*

In the event any covered defect is discovered, the owner must, at his/her own expense, bring the vehicle to the original installer, or nearest DONMAR Authorized Installation Center for correction. DONMAR will repair or replace [at our option] parts found to be defective and subject to such warranty coverage, provided that they were not damaged by alteration, improper use or application, or neglect. It is the responsibility of the installation center to perform all warranty services.

This warranty does not apply to any DONMAR product which has been subject to: abuse, misuse, improper use, installation or application, negligence, neglect, accident, flood, fire, or acts of God, nor does it cover loss of time, inconvenience, use of the vehicle, or any other indirect or consequential damages. This warranty is void if repairs have been made or attempted by unauthorized parties. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

NO OTHER EXPRESSED OR IMPLIED WARRANTIES ARE GIVEN INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Warranty coverage requires proof of installation date with the original warranty card and/or installation bill of sale.



4949-9 Sunbeam Road • Jacksonville, Florida 32257 • 904/731-3393 • www.donmar.com

form Skyroof860-WtyCard.pmd 12/24

Keep this warranty card with all of your important vehicle records.

LIABILITY

Notwithstanding anything contained in this warranty or in any other material related to SKYROOF Sunroofs to the contrary, DONMAR's liability on defective merchandise is limited to repair or replacement of items found to be defective (subject to inspection), and DONMAR shall in no event be liable for any incidental or other damages as a result of any such defect.

Owner may be subject to labor charges if repaired by other than the original installation center. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

It shall be the responsibility of the installer to determine suitability for each application. The installer shall assume all risks and liability in connection with the sunroof installation.

IMPORTANT WARRANTY INFORMATION

SKYROOF® Model: <input type="checkbox"/> RS (wrap finish) <input type="checkbox"/> RST (trimshell)		VIN:
Vehicle Make	Model	Year
Vehicle Owner		
Address		
City	State	Phone ()
Installation Center		Phone ()
Installer	Install Date	
Signature		

SKYROOF® 860 Spoiler Sunroof Operation & Maintenance

SUNROOF OPERATION

TO OPEN GLASS: Press and hold the open arrow on the switch until the glass panel reaches the desired position, then release the switch. Panel may be stopped in any position from partial vent to full open.

TO CLOSE GLASS: Press and hold the close arrow on the switch until the glass panel reaches the desired position, then release the switch.

EXPRESS OPEN/CLOSE: Sunroof is programmed to operate with a single tap of the switch for full open and full close.

AUTO CLOSE on Ignition off: When you remove the key from the ignition, the sunroof will automatically close.

NOTE: To reprogram the express open/close feature, press and hold the switch to full open and continue holding the switch for 60 seconds then release. Next, press and hold the switch to full close and continue holding the switch for 60 seconds, then release. Tap the switch to test the express open/close functions.



SUNROOF MAINTENANCE

GASKET: Clean the gasket at least twice a year with a clean, damp, lint free cloth. If the seal is very dirty, wipe with a mild detergent solution, then wipe off with clean a damp cloth. *NEVER* apply mineral oil, petroleum jelly or vinyl dressing to your gasket. If the seal is very dry, apply a thin coating of light silicone lubricant spray.

GLASS: Clean the glass panel with a non-ammonia glass cleaner and lint free cloth. Hard water spots can be removed with household white vinegar.

FRAME: The outer main frame is textured polymer. It should be cleaned regularly with a mild detergent solution. Do not apply wax or dressing to the textured finish as it will cause a white chalky buildup [can be removed with a soft brush and mild detergent].

DRIVE MECHANISM: Dirt, grit, salt and debris can cause your sunroof to open or close sluggishly and may cause wear or even failure over time. Make sure your tracks are clean and clear of debris, dirt, etc. Inspect the tracks and remove any debris or dirt by hand, followed by gently wiping with a soft lint-free cloth until the surface is clean. Clean and apply white lithium grease annually to maintain smooth operation.

Your local DONMAR Dealer can clean your sunroof, inspect and adjust the drive, and gasket and send you on your way in no time at all.

SKYROOF® and DONMAR® are registered trademarks of DONMAR Enterprises, Inc., U.S.A.