DONMAR SKYROOF® Gen. Z Pop-Up Sunroofs Warranty

LIMITED 3 YEAR / 36,000 MILE WARRANTY

DONMAR Enterprises, Inc. warrants SKYROOF® Gen.Z Pop-Up Sunroofs against defective materials and workmanship while under normal use and service, to the original purchaser, for the earlier of 3 years or 36,000 miles. The sunroof must be properly installed by an Authorized Professional Installation Center. EXCEPTION: No vandalism or glass breakage will be covered. *No other express or implied warranties are given and this warranty is limited as follows:*

In the event any covered defect is discovered, the owner must, at his/her own expense, bring the vehicle to the original installer, or nearest DONMAR Authorized Installation Center for correction. DONMAR will repair or replace [at our option] parts found to be defective and subject to such warranty coverage, provided that they were not damaged by alteration, improper use or application, or neglect. It is the responsibility of the installation center to perform all warranty services.

This warranty does not apply to any DONMAR product which has been subject to: abuse, misuse, improper use or application, negligence, neglect, accident, flood, fire, or acts of God, nor does it cover loss of time, inconvenience, use of the vehicle, or any other

indirect or consequential damages. This warranty is void if repairs have been made or attempted by unauthorized parties. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

NO OTHER EXPRESSED OR IMPLIED WARRANTIES ARE GIVEN INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

LIABILITY: Notwithstanding anything contained in this warranty or in any other material related to SKYROOF® Sunroofs to the contrary, DONMAR's liability on defective merchandise is limited to repair or replacement of items found to be defective (subject to inspection), and DONMAR shall in no event be liable for any incidental or other damages as a result of any such defect.

Owner may be subject to labor charges if repaired by other than the original installation center. Under no circumstances will labor or installation charges be reimbursed by DONMAR.

It shall be the responsibility of the installer to determine suitability for each application. The installer shall assume all risks and liability in connection with the sunroof installation.

IM	PORTANT	WARRA	NTY IN	FORMATION	
MODEL:	☐ Z1731-B for sh	eet metal roof	☐ Z-1731-B	BF for composite roof	
Vehicle Owne	er				
Address					
Vehicle Make		Model		Year	
Installation Center					
City		State	Pho	one ()	
Sunroof				, ,	
Serial #			Insta	allDate	



DONMAR Enterprises, Inc.

4949 Sunbeam Road, Unit 9 • Jacksonville, FL 32257 http://www.donmar.com

Keep this warranty card with all of your important vehicle records.

DONMAR SKYROOF® Gen. Z Pop-Up Sunroofs Operation and Maintenas

OPERATION

TO OPEN: Rotate the latch knob counter-clockwise into desired position from partial to fully open.

TO CLOSE: Rotate the latch knob clockwise until it reaches the fully closed and locked position. You will feel a hard stop.

MAINTENANCE

- Use only mild non-abrasive, non-ammonia glass cleaners to clean the glass panel.
- Clean heavily soiled sunroof frame with a mild solution of soap and water.
- Clean seal with a damp cloth. You may use a mild solution of soap and water for heavily soiled seal.
- If needed, you may occasionally wipe the seal with 100% silicone spray lubricant on a cloth. Do NOT use petrolium products, vinyl dressings or other chemicals.
- Handle and store the glass panel with care.
- See your local sunroof professional for service.



WARNING

DO NOT REMOVE/REPLACE GLASS WHILE VEHICLE IS MOVING!

Air drag can pull the glass panel from your grip and result in broken glass, sunroof or vehicle damage, or even bodily injury. Please verify that the panel, hinges and handle are properly seated prior to moving the vehicle.

REMOVAL OF THE GLASS PANEL: (1) Rotate the latch knob counterclockwise until the glass is in the fully open position. (2) Release the latch by pressing red tab with a key and push upward until the lock releases (3) Grasp the panel with both hands and tilt upward until the hinges release from the frame. (4) Store the panel in a safe place, free from any object that may scratch or impact the glass. A protective storage bag is recommended.

TO RE-FIT THE GLASS PANEL: (1) Grasp the panel with both hands and position front edge over the main seal at a 45 degree angle. (2) Align front hinge blades to guide slots in the frame. (3) Pivot glass downward, ensuring hinge blades slide into guide slots. (4) Align latch assembly red lock tab with bar on main frame and press until it securely locks over the bar. Rotate the latch knob clockwise to close the the sunroof.





SKYROOF and DONMAR are registered trademarks of DONMAR Enterprises, Inc., USA